



Stainless Steel SS304 SS316 Camlock Quick Couplings

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DEYE
- Certification: ISO9001:2015 PED
- Model Number: DY-QC-03
- Minimum Order Quantity: 10PCS
- Price: USD2-USD25 each
- Packaging Details: carton box+ ply wooden cases or carton+ Pallets
- Delivery Time: 20 days for usual order, 7 days for stocked items
- Payment Terms: T/T, L/C, D/P
- Supply Ability: 1000pcs one month



Product Specification

- Highlight: SS316 Camlock Quick Couplings,
SS304 Camlock Quick Couplings,
Stainless Steel 3 camlock fittings

for more products please visit us on piping-industry.com

Product Description

Stainless Steel SS304 SS316 Camlock Quick Couplings

Camlock fittings offer a secure and leak-free connection, ensuring efficient fluid transfer. The male adapter and female coupler interlock tightly, creating a reliable seal that minimizes the risk of leaks or spills. The camlock quick couplings can be with material of SS304, SS316, SS304L, SS316L, Brass, Aluminum, PP, it is widely use for hose pipe connections at low pressure.

Product Information/Product Description/Basis Information/Specification

Name	Camlock Quick Coupling
Material	stainless steel ANSI 304,316,304L,316, Aluminum, Brass, PP
Size	1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8" 10" 12"
Thread	Thread BSP, BSPT, NPT, DIN259/2999
Type	A, B, C, D, E, F, DC, DP (A, B, D, F with thread, B, C, D, DC with handles)
	Type "A", has a male grooved adapter and a female pipe thread (BSP or NPT thread) of the same size
	Type "B", has a female camlock end and a male pipe thread of the same size
	Type "C", has a female camlock on one end and a male hose tail on the other
	Type "D", has a female camlock end and a female pipe thread of the same size
	Type "E", has a male camlock on one end and a male hose tail on the other
	Type "F", has a male grooved adaptor and a male pipe thread of the same size
Gaskets	NBR, EPDM, Viton, PTFE gasket are all available
Cam levers	We use stainless steel cam levers
Pressure	3/4"-2" 250PSI (17.6bar), 3"-4" 200PSI (14.8bar)
	2 1/2" 225PSI (15.8bar), 6" 150PSI (10.5bar)
Technology	Investment casting, Precision casting, NC machine
Packing	pcs/polybag, polybag/carton, cartons/pallet or according to your requirement
Certificate	ISO9001:2015
Process	CNC machine, Testing equipment

Features /Advantages:

- 1.Simple structure, convenient operation, quick connect and open it.
- 2.compact size, light weight, good sealing and interchangeability.
- 3.Adapt to all kinds of working conditions, widely used in liquid, powder and other medium.
- 4.Joint connected with taper pipe threads, outside taper pipe threads, intubation connection, flange connection, etc.
5. Cam & groove couplings are easy to operate. Camlock consists of two parts - male adapter and female coupler. You just need insert the adapter into the coupler until contact is made with the gasket. Then press down the cam arms simultaneously to produce a uniform gasket compression. During the process of installation, no tools are required and hand pressure is enough. Hence, camlock fittings not only save your time but also the tools and human power.
6. Cam & groove couplings are equipped with PVC suction hoses, lay flat discharge hoses and other low-pressure hoses. It can simplify the operation and save working time greatly. However, cam locks are not suitable for any kind of hose. It is forbidden to be used in compressed air or gas or high-pressure applications.

Types of the cam & groove couplings

Type A Male Adapter X Female	Type B Female Coupler x Male
	
Type C Female Coupler X hose Shank	Type D Female Coupler x Female
	
Type E Male Coupler X Hose Shank	Type F Male Adapter xMale
	
Type DC Dust Cap	Type DP Dust Plug
	

Application and usage

Quick release coupling for low-pressure systems, Suitable for Construction; Fire hydrant; Garden; Farming

Our Service

1. Technical support
2. Raw Material Quality control.
3. Inspection during the production time.
4. Final Test includes Surface, Dimension, PT Test, RT test, ultrasonic Test
5. Test Report each shipment
4. Flexible Delivery terms. EXW FOB CIF CFR DDP DDU
5. Flexible payment Ways: LC. TT. DP
6. Customized Package includes Logo. Cases Dimension.
7. 18 months quality Guarantee time.
9. Free replacement by air if any error founded
10. 24 hours to Feedback your questions

DEYE SHIJIAZHUANG DEYE PIPING INDUSTRY CO., LTD Pipefittings Department)



+8613292824811



sales@deyepiping.com



pip-ing-industry.com

No. 368 Youyi St. Shijiazhuang, Hebei, China