Aluminum SS304 SS316 Camlock Groove Couplings For Camlock Joints

Basic Information

Place of Origin: CHINABrand Name: DEYE

Certification: ISO9001:2015 PED

Model Number: DY-QC-05Minimum Order Quantity: 10PCS

• Price: USD2-USD25 each

Packaging Details: carton box+ ply wooden cases or carton+

Pallets

• Delivery Time: 20 days for usual order, 7 days for stocked

items

Payment Terms: T/T, L/C, D/P
Supply Ability: 1000pcs one month



Product Specification

Material: SS304, SS316, Stainless Steel 201

• Size: 1/4"-6"

• Types: TypeA, TypeB, Type C, Type D, Type E,

Type F, Type DC, Type DP

• Connection: Threaded, NPT, BSPT, Groove, Comlock

Highlight: SS316 Camlock Quick Couplings,
 SS304 Camlock Quick Couplings,

Aluminum cam lock coupling

Product Description

Aluminum SS304 SS316 Camlock Groove Couplings For Camlock Joints

Camlock Couplings Type – D enable pipe and hose connections to be made without the use of hands tools; thus eliminating the difficulty in making threaded connections or aaged connection. Almost instantly connections can be made to an outlet, a faucet, a valve, a tank or coupling lengths of hose. No pipe tightening skills, wrenches or tools are required. A connection is made by simply pushing the handles down to the sides of the coupler.

Product Information/Product Description/Basis Information/Specification

Comlock Types:	Type A, Type B, Type C, Type D, Type E, Type F, Type DC, Type DP, Type DW
Sizes	1/2", 3/4",1",1 1/4", 1 1/2", 2", 2 1/2", 3", 4", 5", 6" 8"10" 12"
Working Pressure	5 kg/cm2 to 20 kg/cm2 (working varies according to the size of coupling)
Material	Aluminium,Bronze, Carbon Steel,S.S.304, S.S.316 PP / Cement,Fertilizers,Fire Fighting Equipment,Ink / Dye /
Application	Paint Industries ,Petrochemical / Refineries / Process Industries, Mining, Oil Drilling Companies
	(offshore / onshore), Railways, Steel Plants, Military, Applications, Pneumatic Conveyors, Oil Blending Plants,
	Automobile manufacturers, Chemical Industries and Furnaces.

Features /Advantages:

- 1. Simple structure, convenient operation, quick connect and open it
- 2. compact size, light weight, good sealing and interchangeability
- 3. Adapt to all kinds of working conditions, widely used in liquid, powder and other medium
- 4. Joint connected with taper pipe threads, outside taper pipe threads, intubation connection, flange connection, etc
- 5. Cam & groove couplings are easy to operate. Camlock consists of two parts male adapter and female coupler. You just need insert the adapter into the coupler until contact is made with the gasket. Then press down the cam arms simultaneously to produce a uniform gasket compression. During the process of installation, no tools are required and hand pressure is enough. Hence, camlock fittings not only save your time but also the tools and human power
- 6. Cam & groove couplings are equipped with PVC suction hoses, lay flat discharge hoses and other low-pressure hoses. It can simplify the operation and save working time greatly. However, cam locks are not suitable for any kind of hose. It is forbidden to be used in compressed air or gas or high-pressure applications

Types of the cam & groove couplings



Application and usage

Quick release coupling for low-pressure systems, Suitable for Construction; Fire hydrant; Garden; Farming

Our Service

- 1. Technical support
- 2. Raw Material Quality control.
- 3. Inspection during the production time.
- 4. Final Test includes Surface, Dimension, PT Test, RT test, ultrasonic Test
- 5. Test Report each shipment
- 4. Flexible Delivery terms. EXW FOB CIF CFR DDP DDU
- 5. Flexible payment Ways: LC. TT. DP
- 6. Customized Package includes Logo. Cases Dimension.
- 7. 18 months quality Guarantee time.
- 9. Free replacement by air if any error founded
- 10. 24 hours to Feedback your questions







sales@deyepiping.com



piping-industry.com